

~~06-03~~-12/15/95-01722  
04.09

**100%  
BASIS OF DESIGN**

**REMEDICATION OF  
PESTICIDE-CONTAMINATED SOIL  
OPERABLE UNIT NO. 11 (SITE 80)  
PARADISE POINT GOLF COURSE  
MAINTENANCE AREA**

**MARINE CORPS BASE, CAMP LEJEUNE  
NORTH CAROLINA**

**CONTRACT TASK ORDER 0274**

**DECEMBER 15, 1995**

*Prepared For:*

**DEPARTMENT OF THE NAVY  
ATLANTIC DIVISION  
NAVAL FACILITIES  
ENGINEERING COMMAND  
*Norfolk, Virginia***

*Under:*

**LANTDIV CLEAN Program  
Contract N62470-89-D-4814**

*Prepared by:*

**BAKER ENVIRONMENTAL, INC.  
*Coraopolis, Pennsylvania***

## TABLE OF CONTENTS

	<u>Page</u>
<b>1.0 INTRODUCTION</b> .....	<b>1-1</b>
1.1 Purpose of the Basis of Design .....	1-1
<b>2.0 BACKGROUND INFORMATION</b> .....	<b>2-1</b>
2.1 Site Description and History .....	2-1
2.2 Results from the Previous Investigation by Halliburton, NUS, 1991 .....	2-2
2.3 Results from the Remedial Investigation by Baker Environmental, Inc., 1994 .....	2-3
2.4 Summary of Risks .....	2-3
2.5 Remediation Levels and the Areas of Concern .....	2-4
2.6 Justification for a TCRA .....	2-5
2.7 Scope of the TCRA .....	2-5
<b>3.0 REMEDIAL ACTION WORK BREAKDOWN STRUCTURE</b> .....	<b>3-1</b>
33.01 Mobilization and Preparatory Work .....	3-1
33.02 Monitoring, Sampling, Testing, and Analysis .....	3-2
33.03 Site Work .....	3-3
33.05 Surface Water Collection and Control .....	3-3
33.07 Air Pollution Collection and Control .....	3-3
33.08 Solids Collection and Containment .....	3-3
33.09 Liquid, Sediment, and Sludge Collection and Containment .....	3-5
33.14 Thermal Treatment .....	3-5
33.19 Disposal (Commercial) .....	3-5
33.20 Site Restoration .....	3-5
33.21 Demobilization .....	3-5
<b>4.0 REFERENCES</b> .....	<b>4-1</b>

### APPENDICES

- A Remediation Level Estimations
- B Construction Schedule Estimates
- C Boring Logs

## **LIST OF TABLES**

- 1 Summary of Pesticides Detected During the Halliburton, NUS Investigation, 1991
- 2 Summary of Pesticides Detected During the RI

## **LIST OF FIGURES**

- 1 Operable Unit No. 11 (Sites 7 and 80), Marine Corps Base, Camp Lejeune
- 2 Site Map, Site 80 - Paradise Point Golf Course Maintenance Area
- 3 Previous Investigation Sampling Locations
- 4 Remedial Investigation Sampling Locations
- 5 Additional Remedial Investigation Sampling Locations in the West/Northwest Area
- 6 Positive Detections of Pesticides in Surface Soil
- 7 Positive Detections of Pesticides in Subsurface Soil
- 8 Positive Detections of Pesticides in Surface Soil in the West/Northwest Area
- 9 Positive Detections of Pesticides in Subsurface Soil in the West/Northwest Area
- 10 Areas of Concern
- 11 Area of Concern in the West/Northwest Area

## **1.0 INTRODUCTION**

This document presents the Basis of Design for the remediation of pesticide-contaminated surface soil at Operable Unit No. 11 (Site 80), Marine Corps Base (MCB), Camp Lejeune, North Carolina. Based on the results of the Remedial Investigation (RI) conducted at Site 80 (Baker Environmental, Inc., 1995), contaminated surface soil may present an imminent threat to human health and the environment. As a result, the remediation of this surface soil is being conducted as a time-critical removal action (TCRA). The TCRA includes excavation of the pesticide-contaminated surface soil and disposal of the soil at an appropriate treatment/disposal facility.

This Basis of Design document has been prepared by Baker Environmental, Inc. (Baker) for presentation to the Department of the Navy (DoN), Naval Facilities Engineering Command, Atlantic Division (LANTDIV), under Navy CLEAN Contract Number N62470 (Contract Task Order 0274). The Remedial Action Contracts Delivery Order Requirements Package Guide, NEESA 20.2-062 dated June 1992 was used as a guidance.

Please note that LANTDIV intends to use a Remedial Action Contractor (RAC) to implement the TCRA. In this document, the terms "RAC" and "Contractor" are used interchangeably.

### **1.1 Purpose of the Basis of Design**

The purpose of the Basis of Design is to present LANTDIV with background data on the project, describe the primary elements of the remedial design, recommend design criteria, and present assumptions and any special requirements that may affect the design. This document is not intended to be part of construction plans or specifications to be utilized by the RAC for execution of the remedial action. Baker assumes no responsibility for the use of this report for any purpose other than the intended uses stated above.

## **2.0 BACKGROUND INFORMATION**

This section presents background information relevant to the TCRA including: 1) a description of Site 80 and its history, 2) results from the 1991 investigation conducted by Halliburton, NUS, 3) results from the 1994-95 RI conducted by Baker, 4) a summary of the site risks, 5) remediation levels and the areas of concern, 6) the justification for a TCRA, and 7) the scope of the TCRA.

### **2.1 Site Description and History**

There are currently 33 Installation Restoration Program (IRP) sites at MCB, Camp Lejeune which have been grouped into 17 Operable Units (OUs). Sites 7 and 80 were grouped together as OU No. 11 due to the close proximity of their geographic locations (see Figure 1). Site 7 is located on the northern bank of Northeast Creek and Site 80 is located on the southern bank of Northeast Creek. In addition to their geographic proximity, previous investigations at both sites detected the presence of pesticides in soil.

Site 80, located northwest of Brewster Boulevard within the Paradise Point Golf Course, is referred to as the Paradise Point Golf Course Maintenance Area. The site consists of a one-acre area which is relatively flat, with a slight slope to the northeast. Site elevations vary from 3 to approximately 26 feet above mean sea level (msl).

Figure 2 presents a site map. As shown, Site 80 contains a machine shop (Building 1916), a maintenance building (Building 600), and a maintenance wash down area consisting of a concrete wash pad and sump. The wash pad is used to clean golf course maintenance equipment and the sump is used to collect water and oil runoff generated from the equipment cleaning. Water and oil collected by the sump travels into an oil/water separation pit located southeast of the wash pad (Baker, 1994).

A drainage ditch is located east of the wash down area. During a March 1994 site reconnaissance, surface water runoff was observed flowing southeast across the site toward the drainage ditch. As shown on Figure 2, groundwater flow direction in the shallow aquifer is generally toward the northeast with a mounding effect near the wash down area.

The northeast portion of the site contains several large soil mounds that are overgrown with small pines. There is an open area located south of the mounds where golf course maintenance debris (i.e., tree limbs, lawn clippings, wooden timbers, and brush piles) is deposited. Evidence of burning operations conducted within this open area was documented during the March 1994 site reconnaissance. These soil mounds were generated from the installation of golf course ponds along the fairways in the late 1980s. It has been reported that wastes were disposed of on or around the mounds. However, the types of waste that were disposed and the exact disposal locations are unknown. Employees of the maintenance garage were instructed not to use the soil from this area for fill material (Baker, 1994).

In addition, old maintenance equipment has been deposited in the open and wooded areas surrounding Building 600. Two drums identified during the March 1994 site reconnaissance, were removed from the site by Activity personnel. These drums were located northeast of Building 600 just across the machine shop road (Baker, 1994). However, the contents of the drums are unknown.

Currently, a mobile trailer is stationed within the west/northwest portion of the site (i.e., the area located north of the machine shop road and east of the golf course road). Base personnel reported that a leach field associated with the golf course's sanitary sewer system is also located within this area (see Figure 2). However, the exact location of the leach field is not known. Based on an average groundwater elevation of 13 feet below ground surface (bgs) in this area, the leach field is most likely located at a shallow depth.

The Paradise Point Golf Course was constructed in the 1940s and Building 1916 was constructed in 1946. Reportedly, Site 80 has been used as a maintenance area since the initial construction of the golf course. Today, the maintenance area is still in operation. Current golf course maintenance operations include the machine shop (a potential source of waste oils), the equipment wash down area (a potential source of contaminated washwater), and the routine spraying of pesticides and herbicides.

## **2.2 Results from the Previous Investigation by Halliburton, NUS, 1991**

In June 1991, Halliburton, NUS conducted surface soil, subsurface soil, groundwater, surface water, and sediment investigations at Site 80. Figure 3 identifies the sampling locations associated with

these investigations. Surface soil and subsurface soil were the only environmental media that contained pesticides. Table 1 summarizes the analytical results for the detected pesticides.

### **2.3 Results from the Remedial Investigation by Baker Environmental, Inc., 1994**

In October 1994, Baker initiated an RI consisting of surface soil, subsurface soil, and groundwater investigations. Figure 4 identifies the locations of samples that were collected from October through December 1994. From June through July 1995, an additional round of soil and groundwater samples were collected to further characterize the west/northwest portion of the site. Figure 5 identifies the locations of these additional samples.

Table 2 summarizes the analytical results for pesticides that were detected during the RI. Figures 6 and 7 present the positive detections of pesticides in surface and subsurface soil samples, respectively, collected during the initial round of RI sampling. Figures 8 and 9 present the positive detections of pesticides in surface and subsurface soil samples, respectively, collected during the additional sampling round in the west/northwest area. Please note that subsurface soil samples were not collected from the center of the west/northwest area to avoid contact with the underground leach field.

### **2.4 Summary of Risks**

During the RI, a baseline risk assessment (BRA) and an ecological risk assessment (ERA) were conducted. The following risk values associated with surface soil exposure exceeded acceptable limits:

- A hazard index (HI) of 1.9 for the future child resident. This risk was primarily driven by dieldrin, arsenic, and 4,4'-DDT, and to a lesser extent by aldrin, alpha-chlordane, gamma-chlordane, aluminum, manganese, mercury, and beryllium.
- An incremental cancer risk (ICR) value of  $1.7 \times 10^{-4}$  for the current civilian adult base personnel. This risk was primarily driven by dieldrin, arsenic, and 4,4'-DDD, and to a lesser extent by aldrin, 4,4'-DDT, alpha-chlordane, gamma-chlordane, and beryllium.

- A quotient index (QI) of 1.67 for the cottontail rabbit. This risk was completely driven by dieldrin.

All other risk values associated with surface soil exposure were within acceptable limits.

Pesticides were detected in subsurface soil samples and groundwater samples collected from Site 80. However, the TCRA will not address these media for the following reasons: 1) pesticides in subsurface soil and groundwater did not generate unacceptable risks, and 2) removing the pesticide-contaminated surface soil is expected to reduce elevated pesticide concentrations in the subsurface soil and groundwater (i.e., the surface soil appears to be the source of the pesticides detected in the subsurface soil and groundwater).

## 2.5 Remediation Levels and the Areas of Concern

Because pesticides in surface soil contributed to unacceptable risks, remediation levels were developed based on the current civilian adult worker scenario and a point of departure of  $1 \times 10^{-6}$ . (Appendix A contains the parameters that were used to calculate the remediation levels.) The following table identifies the remediation levels and maximum detected concentrations for the contaminants of concern.

Contaminant of Concern	Remediation Level (ppb)	Maximum Concentration (ppb)
Aldrin	35	49
Dieldrin	37	5,600
4,4'-DDD	2,484	260,000
4,4'-DDT	1,753	40,000
alpha-Chlordane	459	670
gamma-Chlordane	459	640

Based on sampling locations where these pesticides exceeded their remediation levels, areas of concern were identified as shown on Figure 10. In addition, Figure 11 presents a more detailed view



of the area of concern located in the west/northwest area of the site. The horizontal and vertical extents of these areas of concern are not completely defined. As a result, confirmatory soil sampling will be conducted during the execution of the TCRA to ensure that all contaminated soil is collected. For cost estimating purposes, it is assumed that the areas of concern extend horizontally to the limits identified on Figures 10 and 11, and vertically to 1 foot bgs.

## **2.6 Justification for a TCRA**

Pesticide-contaminated surface soil will be addressed by a TCRA for the following reasons:

- Based on the volume of contaminated material, approximately 520 cubic yards, a TCRA should be easy to implement.
- The contaminated surface soil presents an imminent threat to human health and the environment. There are no access restrictions to Site 80 and it continues to serve as an active maintenance area. Therefore, a quick removal action is appropriate.
- When the areas of concern are removed, risk values associated with surface soil exposure will be within acceptable limits determined by the USEPA.

## **2.7 Scope of the TCRA**

The scope of the TCRA encompasses the excavation of pesticide-contaminated surface soil at Site 80 (i.e., the areas of concern identified on Figure 10), and the disposal of this soil at an appropriate treatment/disposal facility.

In order to compare and contrast different costing options, two cost estimates have been compiled for the TCRA. Cost estimate A addresses the remediation of only the west/northwest area of concern (see Figure 11). Cost estimate B addresses all areas of concern at Site 80 (see Figure 10), including the west/northwest area of concern. In addition, two construction schedule estimates, A and B, are presented in Appendix B. This Basis of Design Report, and all specifications included under this design package, apply to the remediation of all areas of concern at Site 80.

### **3.0 REMEDIAL ACTION WORK BREAKDOWN STRUCTURE**

The following sections of this Basis of Design describe the removal action by hazardous, toxic, and radiological waste (HTRW) account numbers, as defined by the Remedial Action Delivery Order Requirements Package Guide, NEESA 20.2-062 of June 1992. In addition, a cost estimate is provided under separate cover and Appendix B presents construction schedule estimates.

#### **33.01 Mobilization and Preparatory Work**

Mobilization involves the acquisition, delivery, and setup of equipment, material, and personnel to the work site that are necessary to accomplish the removal action scope of work.

In addition, during the mobilization period, the Contractor shall prepare all necessary pre-construction submittals as described in Section 01010, "General Paragraphs" of the contract specifications. These specifications allow the Contractor up to sixty (60) days to prepare and submit the necessary pre-construction submittals. These submittals include:

- Work Plan
- Environmental Protection Plan
- Site Health and Safety Plan
- Sampling and Analysis Plan

The Contractor shall provide temporary facilities, including an equipment staging area, a decontamination area, a soil stockpile area, and temporary utilities, as necessary to complete the work.

In addition, the Contractor shall be required to coordinate and obtain any necessary construction permits (such as temporary excavation permits) and clearances prior to the start of construction. The Contractor shall also be responsible for coordinating all required inspections by the Base's Public Works Department.

### **33.02 Monitoring, Sampling, Testing, and Analysis**

The Contractor shall be required to submit to LANTDIV for approval a Sampling and Analysis Plan (SAP) describing the proposed sampling, analytical, and quality control procedures for the chemical data collected during the performance of work (see Section 01010, "General Paragraphs" of the contract specifications). The SAP will ensure that all analytical data generated are scientifically accurate and legally defensible. The SAP will describe the quantity, frequency, and location of samples to be collected and analyses to be performed.

The type and quantity of testing shall be based on the requirements set forth in the specifications, the Contractor's Health and Safety Plan (HASP), and the Contractor's Air Monitoring Plan. Additional monitoring, sampling, testing and analyses shall be carried out as required during the project with the approval of the Navy's Technical Representative (NTR).

#### *Soil Sampling*

Confirmatory soil samples shall be collected from the floor and sidewalls of each excavation area and analyzed for target compound list (TCL) pesticides. The analyses results will be compared to the pesticide remediation levels to confirm that all contaminated soil has been removed. If analyses results exceed remediation levels, the NTR will be notified. One confirmation sample shall be collected for every 50 feet, or fraction thereof, along each excavation sidewall, and one sample every 500 square feet, or fraction thereof, along the base of the excavation.

#### *Contractor-Generated Waste*

Characterization samples shall be collected from all Contractor-generated waste (for example, decontamination fluids and ponded water that may collect in the excavation areas) generated during the removal action. These characterization samples will determine the appropriate transportation and disposal requirements. The samples shall be analyzed for full TCL organics and total analyte list (TAL) metals.

### *Testing and Analysis*

The Contractor shall perform analytical testing of samples collected during removal action activities. The Contractor may consider the use of an on site mobile gas chromatograph to test confirmation samples. The Contractor shall adhere to EPA chain-of-custody procedures during the collection, transport, and analysis of all samples. Laboratory analyses of all samples shall conform with accepted Quality Assurance (QA) requirements. All confirmatory soil samples shall be analyzed with a maximum of 48 hours turnaround time to minimize the amount of time the excavations must remain open.

### **33.03 Site Work**

Site work includes all clearing and grubbing, decontamination/equipment staging area preparation, soil stockpile area preparation (if needed), safety fencing construction, silt fencing construction, and removal of the mobile trailer currently stationed on site.

### **33.05 Surface Water Collection and Control**

The Contractor shall be required to provide devices and facilities as necessary to prevent surface water from contacting contaminated materials (e.g., contaminated equipment) during construction activities, and from flowing off-site. The Contractor shall be required to keep all excavated areas dewatered during construction and to collect, sample, analyze, and dispose of any water accumulated in the excavation and staging areas.

### **33.07 Air Pollution Collection and Control**

Dirt roads and other areas disturbed by remediation operations will be treated with water as a dust suppressant. Use of water shall be minimized to prevent development of mud.

### **33.08 Solids Collection and Containment**

The excavation of contaminated soil shall be performed with earth moving equipment, such as excavators and front-end loaders.

The extent of excavation coincides with the areas of concern defined in Section 2.5. The extent of excavation is also indicated on the design drawings. The estimated in-place volume of contaminated soil that will be excavated is 520 cubic yards. This volume is based on a one-foot depth extending over a 14,000 square foot area. Excavation beyond the designated areas of concern shall only be conducted with NTR approval. If contact is made with the underground leach field located in the west/northwest portion of the site, excavation will immediately stop and the NTR and Activity will be immediately notified.

The excavated soil will be transferred directly into dump trucks for transport to the treatment/disposal facility. However, due to the limited capacity of dump trucks and the quantity of soil that must be excavated, it may be necessary to temporarily store the excavated soil on site. If necessary, excavated soil will be placed in a temporary stockpile area located near the excavation area. The stockpile area will be lined with an impervious sheeting and surrounded by a straw bale berm. The stockpile itself, including the surrounding berm, will be covered with 6 mil reinforced polyethylene sheeting. The edges of the sheeting will be secured with weights to keep it in place.

Once the Contractor has excavated to the specified limits, an on-site analysis consisting of a visual inspection will be performed on the surrounding soil at each excavation area. If the visual inspection reveals evidence of pesticide-contaminated soil, the Contractor will consult with the NTR to determine the extent of additional excavation. When the exposed excavation surfaces do not contain visual evidence of contaminated soil, confirmation samples will be collected and analyzed for TCL pesticides at an on-site mobile laboratory.

Within each excavation area, if the analytical results of confirmation sampling exceed remediation levels, the NTR shall determine the next appropriate action to take. (In case further excavation is required, boring logs are provided in Appendix C. The RI Report [Baker, 1995] contains a more comprehensive collection of boring logs for Site 80.) If the analytical results do not exceed remediation levels, the excavation of soil within that area will be considered complete and site restoration will begin.

General construction debris shall be stockpiled for subsequent disposal at the Base sanitary landfill.

### **33.09 Liquid, Sediment, and Sludge Collection and Containment**

The Contractor shall provide a decontamination pad to collect liquids from the decontamination of personnel and construction equipment. The Contractor shall also collect ponded water that may collect in the excavation areas. The resulting fluids shall be collected for analysis and proper disposal or treatment.

### **33.14 Thermal Treatment**

Thermal treatment of the contaminated soil at an off-site facility is anticipated for this project. This treatment shall be conducted at a permitted hazardous waste facility.

### **33.19 Disposal (Commercial)**

Contaminated soil shall be loaded into approved storage containers that are transportable and leak-proof. The loaded waste shall be manifested by a licensed hazardous waste hauler and transported to an approved, permitted treatment or disposal facility.

Contractor-generated waste (e.g., liquids generated through decontamination procedures) shall be containerized, manifested, and transported to an approved treatment or disposal facility.

### **33.20 Site Restoration**

The excavated areas shall be backfilled with clean backfill material from the borrow area at Camp Lejeune, and regraded to the original contours. Then the excavated areas shall be revegetated.

### **33.21 Demobilization**

All temporary facilities, equipment, and supplies acquired for this contract shall be decontaminated and removed from the site upon completion of the remedial action.

Post-construction submittals shall include: 1) a punch list showing correction of all listed items; 2) a letter from the Contractor certifying completion of all contracted work in accordance with the

contract conditions, applicable regulations, and standards of practice; 3) a completed project current condition with an as-built survey for the entire site; 4) submittal, in one collated document, of all quality control daily reports, samples, results of the sample analyses, corrective actions (if required, taken to correct unacceptable deviations from required quality standards), results of corrective actions; problems encountered and resolved, and lessons learned; and, 5) submittal in one collated document of all quality assurance samples, sample analyses results, and corrective actions (if required, taken to correct unacceptable deviations from required quality standards).

The Contractor shall submit a detailed report summarizing the removal action, lessons learned, and recommendations for inclusion in future similar contracts.

#### 4.0 REFERENCES

Baker Environmental, Inc. 1995. Remedial Investigation Report, Operable Unit No. 11 (Site 80), Marine Corps Base, Camp Lejeune, North Carolina. Draft. Prepared for the Department of the Navy, Naval Facilities Engineering Command, Atlantic Division, Norfolk, Virginia.

Baker Environmental, Inc. 1994. Remedial Investigation/Feasibility Study Project Plans for Operable Units Numbers 8, 11, and 12 (Sites 16, 7, 80, and 3), Marine Corps Base, Camp Lejeune, North Carolina. Final. Prepared for the Department of the Navy, Naval Facilities Engineering Command, Atlantic Division, Norfolk, Virginia.

Haliburton, NUS, 1991. Preliminary Draft Site Inspection Report for Site 80 Paradise Point Golf Course. Marine Corps Base, Camp Lejeune, North Carolina.

Naval Energy and Environmental Support Activity (NEESA), and Naval Facilities Engineering Command Contractor's Office, June 1992. Remedial Action Contracts Delivery Order Requirements Package Guide, Parts 1 and 2. NEESA 20.2-062.



**TABLES**

---

TABLE 1

SUMMARY OF PESTICIDES DETECTED DURING  
 THE HALLIBURTON, NUS INVESTIGATION, 1991  
 OPERABLE UNIT NO. 11 (SITE 80)  
 MCB, CAMP LEJEUNE, NORTH CAROLINA

Contaminant	Surface Soil (0-6 inches)		Near Subsurface Soil (0-2 feet)		Subsurface Soil (3-17 feet)	
	No. of Positive Detections/ No. of Samples	Range of Positive Detections	No. of Positive Detections/ No. of Samples	Range of Positive Detections	No. of Positive Detections/ No. of Samples	Range of Positive Detections
Aldrin	0/3	ND	1/7	6.8-220	0/7	ND
alpha-Chlordane	0/3	ND	1/7	60	0/7	ND
4,4'-DDD	1/3	ND	3/7	20-700	0/7	ND
4,4'-DDE	0/3	ND	5/7	16-210	0/7	ND
4,4'-DDT	0/3	ND	4/7	15-290	0/7	ND
Dieldrin	0/3	ND	4/7	16-440	0/7	ND

Notes:

ND - Not detected.

Reference: Halliburton/NUS, 1991

TABLE 2

**SUMMARY OF PESTICIDES DETECTED DURING THE RI  
OPERABLE UNIT NO. 11 (SITE 80)  
MCB, CAMP LEJEUNE, NORTH CAROLINA**

Media	Contaminant	Site Contamination				Distribution
		Min.	Max.	Max. Concentration Location	Detection Frequency	
Surface Soil		(µg/kg)	(µg/kg)			
	Aldrin	5.4	49	80-DPA-SB10-00	7/55	Lawn Area and Open Area, Northwest Area
	Heptachlor Epoxide	2.7J	9.9	80-DPA-SB05-00	2/55	Open Area, Northwest Area
	Dieldrin	1.1J	5,600	80-DPA-SB10-00	38/55	Widespread, Northwest Area
	4,4'-DDE	0.6J	1,500J	80-MW04-00	45/55	Widespread, Northwest Area
	4,4'-DDD	1.5J	260,000	80-DPA-SB03-00	41/55	Widespread, Northwest Area
	4,4'-DDT	1.3J	40,000	80-MW04-00	44/55	Widespread, Northwest Area
	Endrin Ketone	7.7J	7.7J	80-LA-SB07-00	1/55	Lawn Area
	Endrin Aldehyde	5.2J	5.2J	80-DPA-SB05-00	1/55	Northwest Area
	alpha-Chlordane	0.82J	670J	80-DPA-SB10-00	29/55	Scattered, Northwest Area
gamma-Chlordane	1.2J	640J	80-DPA-SB10-00	22/55	Scattered, Northwest Area	
Subsurface Soil	Aldrin	2.6	2.6	80-LA-SB04-06	1/45	Lawn Area
	Dieldrin	0.73J	1.4J	80-OA-SB02-07	4/45	Drum Area, Open Area, Soil Mounds
	4,4'-DDE	1.4J	35	80-OA-SB02-07	7/45	Open Area, Soil Mounds, Northwest
	4,4'-DDD	1.1J	510J	80-MW-04-06	12/45	Lawn Area, Drum Area, Open Area, Soil Mounds, Northwest
	4,4'-DDT	4.7	240	80-MW-04-06	9/45	Lawn Area, Open Area, Northwest
Groundwater		(µg/L)	(µg/L)			
	4,4'-DDD	2.2J	2.2J	80-MW04-01	1/9	Northwest Area
	4,4'-DDT	0.58J	0.58J	80-MW04-01	1/9	Northwest Area

## Notes:

J = estimated value

µg/Kg = microgram per kilogram (ppb)

µg/L = microgram per liter (ppb)

Reference: Baker, 1995

**FIGURES**

---






FIGURE 1  
 OPERABLE UNIT NO. 11 (SITES 7 AND 80)  
 MARINE CORPS BASE, CAMP LEJEUNE

MARINE CORPS BASE, CAMP LEJEUNE  
 NORTH CAROLINA

01722 DD BIZ



274002BD




**Baker**  
Baker Environmental, Inc.

**LEGEND**

- APPROXIMATE DIRECTION OF SHALLOW GROUNDWATER FLOW
- UNIMPROVED ROAD
- TREELINE
- FIRE HYDRANT
- UTILITY POLE

SOURCE: W.K. DICKSON & CO., INC., JANUARY 1995

**FIGURE 2**  
**SITE MAP**  
**SITE 80 - PARADISE POINT GOLF**  
**COURSE MAINTENANCE AREA**  
**MARINE CORPS BASE, CAMP LEJEUNE**  
**NORTH CAROLINA**




274008BD

**Baker**  
Baker Environmental, Inc.

LEGEND	
80-MW01	SHALLOW MONITORING WELL
80SB01	SOIL BORING
80SS01	SURFACE SOIL SAMPLE
80SD01	SEDIMENT SAMPLE
80SW/SD03	SURFACE WATER/SEDIMENT SAMPLE

SOURCE: W.K. DICKSON & CO., INC., JANUARY 1995

**FIGURE 3**  
PREVIOUS INVESTIGATION SAMPLING LOCATIONS  
SITE 80 - PARADISE POINT GOLF  
COURSE MAINTENANCE AREA  
MARINE CORPS BASE, CAMP, LEJEUNE  
NORTH CAROLINA



2740038D

**Baker**  
Baker Environmental, Inc.

**LEGEND**


80-MW04	SHALLOW MONITORING WELL LOCATION
80-MW03IW	INTERMEDIATE MONITORING WELL LOCATION
80-MA-SB01	SOIL BORING LOCATION
80-DA-SB01	SURFACE SOIL BORING LOCATION

SOURCE: W.K. DICKSON & CO., INC., JANUARY 1995

**FIGURE 4**  
**REMEDIAL INVESTIGATION SAMPLING LOCATIONS**  
**SITE 80 - PARADISE POINT**  
**GOLF COURSE MAINTENANCE AREA**

MARINE CORPS BASE, CAMP, LEJEUNE  
NORTH CAROLINA






**LEGEND**

- 80-MW08 SHALLOW MONITORING WELL LOCATION
  - 80-DPA-SB01 SOIL BORING LOCATION
  - 80-DPA-SB05 SURFACE SOIL SAMPLE LOCATION
- SOURCE: W.K. DICKSON & CO., INC., JANUARY 1995

**FIGURE 5**  
**ADDITIONAL REMEDIAL INVESTIGATION**  
**SAMPLING LOCATIONS IN THE**  
**WEST/NORTHWEST AREA**  
**SITE 80 - PARADISE POINT**  
**GOLF COURSE MAINTENANCE AREA**  
**MARINE CORPS BASE, CAMP LEJEUNE**  
**NORTH CAROLINA**



**LEGEND**


80-MW01 MONITORING WELL LOCATION

80-OA-SB01 SOIL BORING LOCATION

NOTE:  
-SAMPLE CONCENTRATIONS SHOWN IN MICROGRAMS PER KILOGRAM (ug/kg).  
SOURCE: W.K. DICKSON & CO., INC., JANUARY 1995

**FIGURE 6**  
POSITIVE DETECTIONS OF  
PESTICIDES IN SURFACE SOIL  
SITE 80 - POINT GOLF COURSE  
MAINTENANCE AREA  
MARINE CORPS BASE, CAMP LEJEUNE  
NORTH CAROLINA

01722 DDB2Z



2740108D

**LEGEND**


80-MW01 MONITORING WELL LOCATION

80-OA-SB01 SOIL BORING LOCATION

**NOTE:**  
 -SAMPLE CONCENTRATIONS SHOWN IN MICROGRAMS PER KILOGRAM (ug/kg).  
 SOURCE: W.K. DICKSON & CO., INC., JANUARY 1995

**FIGURE 7**  
 POSITIVE DETECTIONS OF PESTICIDES IN SUBSURFACE SOIL  
 SITE 80 - POINT GOLF COURSE MAINTENANCE AREA  
 MARINE CORPS BASE, CAMP, LEJEUNE  
 NORTH CAROLINA





**LEGEND**

80-MW08 SHALLOW MONITORING WELL LOCATION

80-DPA-SB01 SOIL BORING LOCATION

80-DPA-SB05 SURFACE SOIL BORING LOCATION

NOTE:  
-SAMPLE CONCENTRATIONS SHOWN IN MICROGRAMS PER KILOGRAM (ug/kg).  
SOURCE: LANTDIV, OCT. 1991

**FIGURE 8**  
POSITIVE DETECTIONS OF PESTICIDES IN SURFACE SURFACE SOIL IN THE WEST/NORTHWEST AREA SITE 80 - PARADISE POINT GOLF COURSE MAINTENANCE AREA MARINE CORPS BASE, CAMP LEJEUNE NORTH CAROLINA



Sample:	80-MW08-05
PESTICIDES/PCBs	
4,4'-DDD	300
4,4'-DDT	21

80-MW08

Sample:	80-DPA-SB18-04
PESTICIDES/PCBs	
4,4'-DDE	19
4,4'-DDT	9.9


Sample:	80-DPA-SB17-03
PESTICIDES/PCBs	
4,4'-DDD	27

Sample:	80-DPA-SB20-04
PESTICIDES/PCBs	
4,4'-DDT	5.8

Sample:	80-DPA-SB08-04
PESTICIDES/PCBs	
4,4'-DDE	7.3
4,4'-DDD	6
4,4'-DDT	42

Sample:	80-DPA-SB03-04
PESTICIDES/PCBs	
4,4'-DDD	94
4,4'-DDT	22

Sample:	80-DPA-SB01-03
PESTICIDES/PCBs	
4,4'-DDD	38
4,4'-DDT	8.8



274007BD


**Baker**  
Baker Environmental, Inc.

**LEGEND**

- 80-MW08 SHALLOW MONITORING WELL LOCATION
- 80-DPA-SB01 SOIL BORING LOCATION
- 80-DPA-SB05 SURFACE SOIL BORING LOCATION

NOTE:  
-SAMPLE CONCENTRATIONS SHOWN IN MICROGRAMS PER KILOGRAM (ug/kg).  
SOURCE: LANTDIV, OCT. 1991

**FIGURE 9**  
POSITIVE DETECTIONS OF PESTICIDES IN SUBSURFACE SOIL IN THE WEST/NORTHWEST AREA  
SITE 80 - PARADISE POINT GOLF COURSE MAINTENANCE AREA  
MARINE CORPS BASE, CAMP LEJEUNE  
NORTH CAROLINA



2740118D

**LEGEND**


- 80-MW01 MONITORING WELL LOCATION
- 80-MA-SB01 SOIL BORING LOCATION
- AREA OF CONCERN

SOURCE: W.K. DICKSON & CO., INC., JANUARY 1995





**FIGURE 10**  
**AREAS OF CONCERN**  
**SITE 80 - PARADISE POINT**  
**GOLF COURSE MAINTENANCE AREA**

MARINE CORPS BASE, CAMP, LEJEUNE  
 NORTH CAROLINA





**LEGEND**

- 80-MW08  SHALLOW MONITORING WELL LOCATION
- 80-DPA-SB01  SOIL BORING LOCATION
- 80-DPA-SB05  SURFACE SOIL SAMPLE LOCATION
-  EXTENT OF AREA OF CONCERN

SOURCE: W.K. DICKSON & CO., INC., JANUARY 1995

**FIGURE 11**  
**AREA OF CONCERN IN THE**  
**WEST/NORTHWEST AREA**  
**SITE 80 - PARADISE POINT GOLF**  
**COURSE MAINTENANCE AREA**  
**MARINE CORPS BASE, CAMP LEJEUNE**  
**NORTH CAROLNA**

**Baker**  
 Baker Environmental, Inc.

**APPENDIX A**  
**REMEDIATION LEVEL ESTIMATIONS**

---



INGESTION OF REMEDIATION LEVEL  
 FEASIBILITY STUDY CTO-0274  
 OPERABLE UNIT NO. 11 (SITE 80)  
 MCB CAMP LEJEUNE  
 CURRENT CIVILIAN EMPLOYEE

$$C = TR \text{ or } THI * BW * ATc \text{ or } ATnc * DY / EF * ED * IR * CF * FI * CSF \text{ or } 1/RfD$$

Where:

- C = contaminant concentration in soil (ug/kg)
- TR = total lifetime carcinogenic risk (unitless)
- THI = total hazard index (unitless)
- CF = conversion for kg to mg
- EF = exposure frequency (days/yr)
- ED = exposure duration (yr)
- IR = soil ingestion rate (mg/day)
- CSF = carcinogenic slope factor
- RfD = reference dose
- FI = fraction ingested from source
- BW = body weight (kg)
- ATc = averaging time for carcinogen (yr)
- ATnc = averaging time for noncarcinogen (yr)
- DY = days per year (days/year)

INPUTS

Calculated
1E-06
1
1E-06
250
25
480
specific
specific
100
70
70
25
365

Note: Inputs are scenario and site specific

Contaminant	Concentration Carcinogen (ug/kg)	Exposure Frequency (days/yr)	Exposure Duration (yr)	Ingestion Rate (mg/day)	Body Weight (kg)	Average Carc Time (years)	Conversion Factor (kg/mg)	Days per year (days/yr)	Lifetime Cancer Risk	Slope Factor (mg/kg/day)-1	Fraction Ingested From Source
Dieldrin	37	250	25	480	70	70	1E-06	365	1E-06	1.60E+01	1
4,4'-DDD	2484	250	25	480	70	70	1E-06	365	1E-06	2.40E-01	1
4,4'-DDT	1753	250	25	480	70	70	1E-06	365	1E-06	3.40E-01	1
Aldrin	35	250	25	480	70	70	1E-06	365	1E-06	1.70E+01	1
alpha-chlordane	459	250	25	480	70	70	1E-06	365	1E-06	1.30E+00	1
gamma-chlordane	459	250	25	480	70	70	1E-06	365	1E-06	1.30E+00	1
Arsenic	397	250	25	480	70	70	1E-06	365	1E-06	1.50E+00	1
Beryllium	139	250	25	480	70	70	1E-06	365	1E-06	4.30E+00	1

Contaminant	Concentration Noncarcinogen (ug/kg)	Exposure Frequency (days/yr)	Exposure Duration (yr)	Ingestion Rate (mg/day)	Body Weight (kg)	Average Noncarc Time (years)	Conversion Factor (kg/mg)	Days per year (days/yr)	Hazard Index	Reference Dose (mg/kg/day)	Fraction Ingested From Source
Dieldrin	10646	250	25	480	70	25	1E-06	365	1	5.00E-05	1
4,4'-DDD	0	250	25	480	70	25	1E-06	365	1	--	1
4,4'-DDT	106458	250	25	480	70	25	1E-06	365	1	5.00E-04	1
Aldrin	6388	250	25	480	70	25	1E-06	365	1	3.00E-05	1
alpha-chlordane	12775	250	25	480	70	25	1E-06	365	1	6.00E-05	1
gamma-chlordane	12775	250	25	480	70	25	1E-06	365	1	6.00E-05	1
Arsenic	63875	250	25	480	70	25	1E-06	365	1	3.00E-04	1
Beryllium	1064583	250	25	480	70	25	1E-06	365	1	5.00E-03	1

**APPENDIX B**  
**CONSTRUCTION SCHEDULE ESTIMATES**

---





**APPENDIX C**  
**BORING LOGS**

---

# BAKER

## TEST BORING LOG

BOREHOLE NUMBER:

80-0A-SB01

SHEET: 1 OF: 1

PROJECT NUMBER: 62-170-274  
 PROJECT NAME: SITE 80 - PARADISE POINT GOLF COURSE MAINTENANCE AREA  
 LOCATION: NCB CAMP LEJEUNE, NC  
 DRILLING COMPANY: -  
 RIG TYPE & NUMBER: -  
 DRILLING METHOD: HAND AUGERS  
 WEATHER: SUNNY  
 GEOLOGIST: E.J. KLEINKAUF  
 ENV. SCIENTIST: M.D. SMITH  
 DATE BEGUN: 11/3/94 DATE COMPLETED: 11/3/94

GROUND SURFACE ELEVATION: 16.22' msl  
 TOTAL DEPTH: 1.0' bgs

ELEVATION	DEPTH	SOIL SAMPLES	SAMPLE NO.	SAMPLE METHOD	BLOWS/FS	RECOVERY	PID (PPH)		LITHOLOGY	DESCRIPTION	DEPTH
							BG	FS			
16:00	0.0		S-1	HA	-	-	0.0	0.0		SILTY SAND: Fine grained, trace of root material at surface, trace to little clay, dark brown/brown, damp, very loose to medium dense	0.0
15:00	1.0										1.0
14:00	2.0										2.0
13:00	3.0										3.0
12:00	4.0										4.0
11:00	5.0										5.0
10:00	6.0										6.0
9:00	7.0										7.0
8:00	8.0										8.0
7:00	9.0										9.0
6:00	10.0										10.0
5:00	11.0										11.0
4:00	12.0										12.0
3:00	13.0										13.0
2:00	14.0										14.0
1:00	15.0										15.0
0:00	16.0										16.0
1:00	17.0										17.0
2:00	18.0										18.0
3:00	19.0										19.0
4:00	20.0										20.0
5:00	21.0										21.0
6:00	22.0										22.0
7:00	23.0										23.0
8:00	24.0										24.0
9:00	25.0										25.0
10:00	26.0										26.0
11:00	27.0										27.0
12:00	28.0										28.0

BOTTOM OF BOREHOLE = 1.0'







BAKER

TEST BORING LOG

BOREHOLE NUMBER

80-OPA-SB20

SHEET: 1 OF: 1

PROJECT NUMBER: 62470-274  
 PROJECT NAME: SITE 80 - PARADISE POINT GOLF COURSE MAINTENANCE AREA  
 LOCATION: MOB CAMP LEJEUNE, NC  
 DRILLING COMPANY: PARRATT-WOLFF, INC.  
 RIG TYPE & NUMBER: TRUCK RIG - CHE 55  
 DRILLING METHOD: HOLLOW STEM AUGERS  
 WEATHER: SUNNY, WARM  
 GEOLOGIST: H.K. DEJOHN  
 ENV SCIENTIST:  
 DATE BEGUN: 6/14/95 DATE COMPLETED: 6/14/95

GROUND SURFACE ELEVATION: 11.90' msl  
 TOTAL DEPTH: 11.0' bgs

ELEVATION	DEPTH	SOIL SAMPLES	SAMPLE NO.	SAMPLE METHOD	BLOGS/6"	RECOVERY	PID (PPM)		LITHOLOGY	DESCRIPTION	DEPTH
							BG	PS			
0.0	0.0		S-1	HR	-	-	1.0	1.0	Dotted pattern	SAND: fine grained, some silt, little to some clay, gray/brown, wet to moist, soft	0.0
1.0	S-2		SS	1	1.3	1.0	1.0	2.0			
2.0	S-3		SS	2	1.0	0.9	0.9	Diagonal hatching	CLAY: some to trace silt, little to some fine grained sand 3-10', brown/gray, moist to wet, medium stiff to very soft	3.0	
3.0	S-4		SS	1	1.1	0.5	0.5			4.0	
4.0	S-5		SS	1	1.1	0.5	0.5			5.0	
5.0	S-6		SS	1	1.5	0.5	0.5			6.0	
6.0	7.0									7.0	
7.0	8.0									8.0	
8.0	9.0									9.0	
9.0	10.0									10.0	
10.0	11.0									11.0	
11.0	12.0									12.0	
12.0	13.0									13.0	
13.0	14.0									14.0	
14.0	15.0									15.0	
15.0	16.0									16.0	
16.0	17.0									17.0	
17.0	18.0									18.0	
18.0	19.0									19.0	
19.0	20.0									20.0	
20.0	21.0									21.0	
21.0	22.0									22.0	
22.0	23.0									23.0	
23.0	24.0									24.0	
24.0	25.0									25.0	
25.0	26.0									26.0	
26.0	27.0									27.0	
27.0	28.0									28.0	

BOTTOM OF BOREHOLE = 11.0'

NOTES:

1) Groundwater encountered at 7.0' during drilling.

BAKER

TEST BORING LOG

BOREHOLE NUMBER:

80-DPA-SB17

SHEET: 1 OF: 1

PROJECT NUMBER: 62470-274  
 PROJECT NAME: SITE 80 - PARADISE POINT GOLF COURSE MAINTENANCE AREA  
 LOCATION: HCB CAMP LEJEUNE, NC  
 DRILLING COMPANY: PARRATT-WOLFF, INC.  
 RIG TYPE & NUMBER: TRUCK RIG - CME 55  
 DRILLING METHOD: HOLLOW STEM AUGERS  
 WEATHER: SUNNY, WARM  
 GEOLOGIST: M.K. DEJOHN  
 ENV. SCIENTIST:  
 DATE BEGUN: 6/14/95 DATE COMPLETED: 6/14/95

GROUND SURFACE ELEVATION: 12.80' msl  
 TOTAL DEPTH: 11.0' bgs

ELEVATION	DEPTH	SOIL SAMPLES	SAMPLE NO.	SAMPLE METHOD	BLOWS/6"	RECOVERY	PIU (PPH)		LITHOLOGY	DEPTH
							BG	PS		
12:00	0.0		S-1	HH	-	-	1.0	1.0	SAND: Fine grained, some silt, little clay 0-1 1/3-5', some rock fragments 1-3', gray to dark gray, damp, loose to medium stiff	0.0
11:00	1.0		S-2	SS	3	4	0.9	0.6		1.0
10:00	2.0		S-3	SS	3	3	1.5	0.6		2.0
9:00	3.0		S-3	SS	3	2	1.5	0.6	3.0	
8:00	4.0		S-3	SS	3	3	1.5	0.6	4.0	
7:00	5.0		S-4	SS	1	3	2.0	0.6	5.0	
6:00	6.0		S-4	SS	3	4	2.0	0.6	6.0	
5:00	7.0		S-5	SS	4	4	1.7	0.5	7.0	
4:00	8.0		S-5	SS	4	6	1.7	0.5	8.0	
3:00	9.0		S-5	SS	2	7	1.5	0.5	9.0	
2:00	10.0		S-6	SS	2	10	1.5	0.5	10.0	
1:00	11.0					12				11.0
0:00	12.0	SAND: Fine grained, some silt, little clay, brown, wet, medium dense								12.0
15:00	28.0	BOTTOM OF BOREHOLE = 11.0'								28.0
		NOTES: 1) Groundwater encountered at 10.0' during drilling.								

BAKER

TEST BORING LOG

BOREHOLE NUMBER:

80-LA-SB01

SHEET: 1 OF: 1

PROJECT NUMBER: 62470-274  
 PROJECT NAME: SITE 80 - PARADISE POINT GOLF COURSE MAINTENANCE AREA  
 LOCATION: HCB CAMP LEJEUNE, NC  
 DRILLING COMPANY: HARDIN-HUBER, INC.  
 RIG TYPE & NUMBER: ATV  
 DRILLING METHOD: HOLLOW STEM AUGERS  
 WEATHER: SUNNY  
 GEOLOGIST: E.J. KLEINKAUF/J.E. ZIMMERMAN  
 ENV. SCIENTIST:  
 DATE BEGUN: 11/5/94 DATE COMPLETED: 11/5/94

GROUND SURFACE ELEVATION: 14.58' msl  
 TOTAL DEPTH: 13.0' bgs

ELEVATION	DEPTH	SOIL SAMPLES	SAMPLE NO.	SAMPLE METHOD	BLOWS/5'	RECOVERY	PTD (PPH)		LITHOLOGY	DEPTH	
							BG	PS			
14:00	0.0		S-1	SS	-	-	0.2	0.2		0.0	
13:00	1.0		S-2	SS	-	-	0.2	0.2		SILTY SAND: fine grained, trace coarse gravel, root material at surface, dark brown/brown, damp, very loose (probable fill to approx. 1')	1.0
12:00	2.0		S-3	SS	-	-	0.2	0.2			2.0
11:00	3.0		S-4	SS	-	-	0.2	0.2			3.0
10:00	4.0		S-5	SS	-	-	0.2	0.2			4.0
9:00	5.0		S-6	SS	-	-	0.2	0.2			5.0
8:00	6.0		S-7	SS	-	-	0.2	0.2			6.0
7:00	7.0		S-8	SS	-	-	0.2	0.2		SILTY CLAY: some fine grained sand, brown, damp, very loose	7.0
6:00	8.0		S-9	SS	-	-	0.2	0.2			8.0
5:00	9.0		S-10	SS	-	-	0.2	0.2			SILTY SAND: fine grained, some to little clay, light gray/light brown, damp to wet, very loose
4:00	10.0		S-11	SS	-	-	0.2	0.2		10.0	
3:00	11.0		S-12	SS	-	-	0.2	0.2		11.0	
2:00	12.0		S-13	SS	-	-	0.2	0.2		12.0	
1:00	13.0								13.0		
0:00	14.0								14.0		
1:00	15.0								15.0		
2:00	16.0								16.0		
3:00	17.0								17.0		
4:00	18.0								18.0		
5:00	19.0								19.0		
6:00	20.0								20.0		
7:00	21.0								21.0		
8:00	22.0								22.0		
9:00	23.0								23.0		
10:00	24.0								24.0		
11:00	25.0								25.0		
12:00	26.0								26.0		
13:00	27.0								27.0		
	28.0								28.0		

BOTTOM OF BOREHOLE = 13.0'  
 NOTES:  
 1) Groundwater encountered at 12.5' during drilling.







BAKER

TEST BORING LOG

BOREHOLE NUMBER:

80-LA-SB05

SHEET 1 OF 1

PROJECT NUMBER: 62-170-274  
 PROJECT NAME: SITE 80 - PARADISE POINT GOLF COURSE MAINTENANCE AREA  
 LOCATION: MCB CAMP LEJEUNE, NC  
 DRILLING COMPANY: HARDIN-HUBER, INC.  
 RIG TYPE & NUMBER: ATV  
 DRILLING METHOD: HOLLOW STEM AUGERS  
 WEATHER: SUNNY  
 GEOLOGIST: J.E. ZIMMERMAN  
 ENV. SCIENTIST: M.K. DEJOHN  
 DATE BEGUN: 11/1/94 DATE COMPLETED: 11/1/94

GROUND SURFACE ELEVATION: 14.65' msl  
 TOTAL DEPTH: 15.0' bgs

ELEVATION	DEPTH	SOIL SAMPLES	SAMPLE NO.	SAMPLE METHOD	BLOIS/S"	RECOVERY	PID (PPH)		LITHOLOGY	DESCRIPTION	DEPTH
							BG	PS			
14.00	0.0		S-1	SS	-	-	-	-		SILTY SAND: fine grained, root material at surface, trace clay, dark brown/brown/light brown, damp, very loose to medium dense	0.0
13.00	1.0		S-2	SS	4	1.1	0.5	0.5			1.0
12.00	2.0				5						2.0
11.00	3.0				4						3.0
10.00	4.0		S-3	SS	5	1.5	0.5	0.5			4.0
9.00	5.0				7						5.0
8.00	6.0		S-4	SS	8	1.3	0.5	0.5			6.0
7.00	7.0				12						7.0
6.00	8.0		S-5	SS	6	1.3	0.5	0.5		SILTY CLAY: trace fine grained sand, light gray, damp, stiff/medium stiff	8.0
5.00	9.0				8						9.0
4.00	10.0		S-6	SS	7	1.4	0.5	0.5		SILTY SAND: fine grained, trace clay, brown/light brown/light gray, damp to wet, medium dense	10.0
3.00	11.0				10						11.0
2.00	12.0		S-7	SS	6	1.5	0.5	0.5			12.0
1.00	13.0				7						13.0
0.00	14.0		S-8	SS	3	1.5	0.5	0.5			14.0
	15.0				5						15.0
	16.0				8						16.0
	17.0				11						17.0
	18.0										18.0
	19.0										19.0
	20.0										20.0
	21.0										21.0
	22.0										22.0
	23.0										23.0
	24.0										24.0
	25.0										25.0
	26.0										26.0
	27.0										27.0
	28.0										28.0

BOTTOM OF BOREHOLE = 15.0'  
 NOTES  
 1) Groundwater encountered at 14.0' during drilling





BAKER

TEST BORING LOG

BOREHOLE NUMBER:

80-LA-SB07

SHEET: 1 OF: 1

PROJECT NUMBER: 62470-274  
 PROJECT NAME: SITE 80 - PARADISE POINT GOLF COURSE MAINTENANCE AREA  
 LOCATION: HCB CAMP LEJEUNE, NC  
 DRILLING COMPANY: HARDIN-HUBER, INC  
 RIG TYPE & NUMBER: ATV  
 DRILLING METHOD: HOLLOW STEM AUGERS  
 WEATHER: SUNNY  
 GEOLOGIST: J. E. ZIMMERMAN  
 ENV. SCIENTIST: L. H. JOHNSON  
 DATE BEGUN: 11/2/94 DATE COMPLETED: 11/2/94

GROUND SURFACE ELEVATION: 13.59' msl  
 TOTAL DEPTH: 15.0' bgs

ELEVATION	DEPTH	SOIL SAMPLES	SAMPLE NO.	SAMPLE METHOD	BLOWS/6"	RECOVERY	PID (PPM)		LITHOLOGY	DESCRIPTION	DEPTH
							BG	PS			
13.00	0.0		S-1	SS	-	-	-	-		SILTY SAND: fine grained, trace root material at surface, trace to little clay, dark brown/brown/light brown/light gray, damp, very loose/loose/medium dense	0.0
12.00	1.0		S-2	SS	2	1.2	0.2	0.2			1.0
11.00	2.0		S-3	SS	2 4 5	1.6	0.2	0.2			2.0
10.00	3.0		S-4	SS	2 6 8	1.6	0.2	0.2			3.0
9.00	4.0		S-5	SS	7 11 10 11	1.7	0.2	0.2			4.0
8.00	5.0		S-6	SS	11 10 15 13	1.6	0.2	0.2			5.0
7.00	6.0		S-7	SS	5 7 8 12	1.6	0.2	0.2		SILTY CLAY: trace fine grained sand, light gray, damp, stiff	6.0
6.00	7.0		S-8	SS	11 9 6 7	1.6	0.2	0.2		SILTY SAND: fine grained, light gray, damp to wet, medium dense	7.0
5.00	8.0		S-9	SS	2 4 6 7	1.6	0.2	0.2			8.0
4.00	9.0										9.0
3.00	10.0										10.0
2.00	11.0										11.0
1.00	12.0										12.0
0.00	13.0										13.0
1.00	14.0										14.0
2.00	15.0										15.0
3.00	16.0										16.0
4.00	17.0										17.0
5.00	18.0										18.0
6.00	19.0										19.0
7.00	20.0										20.0
8.00	21.0										21.0
9.00	22.0										22.0
10.00	23.0										23.0
11.00	24.0										24.0
12.00	25.0										25.0
13.00	26.0										26.0
14.00	27.0										27.0
	28.0										28.0

BOTTOM OF BOREHOLE = 15.0'

NOTES:

- 1) Groundwater encountered at 14.0' during drilling.

BAKER

TEST BORING LOG

BOREHOLE NUMBER:

80-MA-SB01

SHEET 1 OF 1

PROJECT NUMBER: 62470-274  
 PROJECT NAME: SITE 80 - PARADISE POINT GOLF COURSE MAINTENANCE AREA  
 LOCATION: MCB CAMP LEJEUNE, NC  
 DRILLING COMPANY: HARDIN-HUBER, INC.  
 RIG TYPE & NUMBER: ATV  
 DRILLING METHOD: HOLLOW STEM AUGERS  
 WEATHER: SUNNY  
 GEOLOGIST: J.E. ZIMMERMAN  
 ENV. SCIENTIST: M.K. DEJOHN  
 DATE BEGUN: 11/2/94 DATE COMPLETED: 11/2/94

GROUND SURFACE ELEVATION: 14.73' msl  
 TOTAL DEPTH: 15.0' bgs

ELEVATION	DEPTH	SOIL SAMPLES	SAMPLE NO.	SAMPLE METHOD	BLDS/S	RECOVERY	PID (PPM)		LITHOLOGY	DESCRIPTION	DEPTH	
							BG	PS				
14.00	0.0		S-1	SS	-	-	-	-		SILTY SAND: fine grained, trace coarse gravel and root material at surface, trace clay, dark brown/brown, damp, very loose to medium dense	0.0	
13.00	1.0		S-2	SS	2	1	1.7	0.2		0.2	1.0	
12.00	2.0					2					2.0	
11.00	3.0					3					3.0	
10.00	4.0		S-3	SS	2	4	1.3	0.2		0.2	4.0	
9.00	5.0					5					5.0	
8.00	6.0		S-4	SS	4	7	0.8	0.2		0.2	SILTY CLAY: trace fine grained sand, brown/light gray /light brown, damp to moist, medium stiff	6.0
7.00	7.0					7					7.0	
6.00	8.0		S-5	SS	2	4	1.7	0.2		0.2	8.0	
5.00	9.0					6					9.0	
4.00	10.0		S-6	SS	3	6	1.8	0.2		0.2	10' to 11' SAND Fine grained, trace to little clay	10.0
3.00	11.0					10					11.0	
2.00	12.0		S-7	SS	2	2	2.0	0.2		0.2	12.0	
1.00	13.0					5					13.0	
0.00	14.0		S-8	SS	1	1	1.4	0.2		0.2	SILTY SAND: fine grained, light gray, moist to wet, loose	14.0
	15.0				5				15.0			
1.00	16.0	BOTTOM OF BOREHOLE = 15.0'									16.0	
2.00	17.0	NOTES: 1) Groundwater encountered at 14.0' during drilling									17.0	
3.00	18.0										18.0	
4.00	19.0										19.0	
5.00	20.0										20.0	
6.00	21.0										21.0	
7.00	22.0										22.0	
8.00	23.0										23.0	
9.00	24.0										24.0	
10.00	25.0										25.0	
11.00	26.0										26.0	
12.00	27.0										27.0	
13.00	28.0										28.0	







BAKER

TEST BORING LOG

BOREHOLE NUMBER

80-0A-SB01

SHEET: 1 OF 1

PROJECT NUMBER: 62470-274  
 PROJECT NAME: SITE 80 - PARADISE POINT GOLF COURSE MAINTENANCE AREA  
 LOCATION: HCB CAMP LEJEUNE, NC  
 DRILLING COMPANY: HARDIN-HUBER, INC.  
 RIG TYPE & NUMBER: ATV  
 DRILLING METHOD: HOLLOW STEM AUGERS  
 WEATHER: SUNNY  
 GEOLOGIST: J.E. ZIMMERMAN  
 ENV. SCIENTIST: L.H. JOHNSON  
 DATE BEGUN: 11/3/94 DATE COMPLETED: 11/3/94

GROUND SURFACE ELEVATION 17.47' msl  
 TOTAL DEPTH: 17.0' bgs

ELEVATION	DEPTH	SOIL SAMPLES	SAMPLE NO.	SAMPLE METHOD	BLONS/S*	RECOVERY	PID (PPM)		LITHOLOGY	DESCRIPTION	DEPTH
							BG	PS			
17.00	0.0		S-1	SS	-	-	-	-	SILTY SAND: fine grained, trace wood at surface, trace to little clay, dark brown/brown, damp, very loose to medium dense	0.0	
16.00	1.0		S-2	SS	4	8	1.8	0.2		0.5	1.0
15.00	2.0		S-3	SS	4	8	1.8	0.2		0.5	2.0
14.00	3.0		S-3	SS	4	14	0.9	0.2	0.2	SILTY CLAY trace fine grained sand, light gray, damp, stiff	3.0
13.00	4.0		S-4	SS	4	9	1.8	0.2	0.2		4.0
12.00	5.0		S-4	SS	4	5	1.8	0.2	0.2		5.0
11.00	6.0		S-5	SS	1	3	1.6	0.2	0.2	SAND: fine grained, trace silt, light brown/light gray, damp to wet, medium dense	6.0
10.00	7.0		S-5	SS	1	5	1.6	0.2	0.2		7.0
9.00	8.0		S-6	SS	2	8	1.7	0.2	0.2		8.0
8.00	9.0	S-6	SS	2	6	1.7	0.2	0.2	SAND: fine grained, trace silt, light brown/light gray, damp to wet, medium dense	9.0	
7.00	10.0	S-7	SS	3	13	1.3	0.3	0.3		10.0	
6.00	11.0	S-7	SS	3	13	1.3	0.3	0.3		11.0	
5.00	12.0	S-8	SS	2	5	1.5	0.2	0.2	SAND: fine grained, trace silt, light brown/light gray, damp to wet, medium dense	12.0	
4.00	13.0	S-8	SS	2	15	1.5	0.2	0.2		13.0	
3.00	14.0	S-8	SS	2	5	1.5	0.2	0.2		14.0	
2.00	15.0	S-9	SS	5	7	1.2	0.2	0.2	SAND: fine grained, trace silt, light brown/light gray, damp to wet, medium dense	15.0	
1.00	16.0	S-9	SS	5	7	1.2	0.2	0.2		16.0	
0.00	17.0	S-9	SS	5	12	1.2	0.2	0.2		17.0	
18.00	18.0	BOTTOM OF BOREHOLE = 17.0'									18.0
19.00	19.0	NOTES: 1) Groundwater encountered at 15.5' during drilling									19.0
20.00	20.0										20.0
21.00	21.0										21.0
22.00	22.0										22.0
23.00	23.0										23.0
24.00	24.0										24.0
25.00	25.0										25.0
26.00	26.0										26.0
27.00	27.0										27.0
28.00	28.0										28.0



BAKER

TEST BORING LOG

BOREHOLE NUMBER:

80-0A-SB03

SHEET: 1 OF: 1

PROJECT NUMBER: 62470-274  
 PROJECT NAME: SITE 80 - PARADISE POINT GOLF COURSE MAINTENANCE AREA  
 LOCATION: MCB CAMP LEJEUNE, NC  
 DRILLING COMPANY: HARDIN-HUBER, INC.  
 RIG TYPE & NUMBER: ATV  
 DRILLING METHOD: HOLLOW STEM AUGERS  
 WEATHER: SUNNY  
 GEOLOGIST: J.E. ZIMMERMAN  
 ENV. SCIENTIST: L.H. JOHNSON  
 DATE BEGUN: 11/3/94 DATE COMPLETED: 11/3/94

GROUND SURFACE ELEVATION: 16.73' msl  
 TOTAL DEPTH: 17.0' bgs

ELEVATION	DEPTH	SOIL SAMPLES	SAMPLE NO.	SAMPLE METHOD	BLMS/6"	RECOVERY	PID (PPM)		LITHOLOGY	DESCRIPTION	DEPTH
							86	PS			
16:00	0.0		S-1	SS	-	-	0.3	0.3		SILTY SAND: Fine grained, trace wood at surface, trace to little clay, dark brown/brown, damp, very loose/medium dense	0.0
15:00	1.0		S-2	SS	8	0.9	0.2	0.2			1.0
14:00	2.0				5						2.0
13:00	3.0		S-3	SS	7	1.1	0.2	0.2			3.0
12:00	4.0				11						4.0
11:00	5.0		S-4	SS	3	1.8	0.2	0.2			5.0
10:00	6.0				3						6.0
9:00	7.0		S-5	SS	4	1.2	0.3	0.3		7 to 7.5' SILTY CLAY: trace fine grained sand	7.0
8:00	8.0				5					SAND: Fine grained, trace silt, light brown/light gray, damp to wet, medium dense	8.0
7:00	9.0		S-6	SS	2	1.2	0.2	0.2			9.0
6:00	10.0				6						10.0
5:00	11.0		S-7	SS	3	1.4	0.3	0.3			11.0
4:00	12.0				4						12.0
3:00	13.0		S-8	SS	5	1.5	0.2	0.2			13.0
2:00	14.0				7						14.0
1:00	15.0		S-9	SS	2	1.3	0.2	0.2			15.0
0:00	16.0				2						16.0
1:00	17.0				7						17.0
1:00	17.0				10						17.0
1:00	18.0										18.0
2:00	19.0										19.0
3:00	20.0										20.0
4:00	21.0										21.0
5:00	22.0										22.0
6:00	23.0										23.0
7:00	24.0										24.0
8:00	25.0										25.0
9:00	26.0										26.0
10:00	27.0										27.0
11:00	28.0										28.0

BOTTOM OF BOREHOLE = 17.0'

NOTES:

1) Groundwater encountered at 15.5' during drilling.





<b>BAKER</b>	<b>TEST BORING LOG</b>	BOREHOLE NUMBER:
		80-0A-SB05
		SHEET: 1 OF 1

PROJECT NUMBER:	62470-274	GROUND SURFACE ELEVATION:	16.76' msl
PROJECT NAME:	SITE 80 - PARADISE POINT GOLF COURSE MAINTENANCE AREA	TOTAL DEPTH:	15.0' bgs
LOCATION:	MCB CAMP LEJEUNE, NC		
DRILLING COMPANY:	HARDIN-HUBER, INC.		
RIG TYPE & NUMBER:	ATV		
DRILLING METHOD:	HOLLOW STEM AUGERS		
WEATHER:	SUNNY		
GEOLOGIST:	H.K. DEJOHN		
ENV SCIENTIST:	H.D. SMITH		
DATE BEGUN:	11/4/94	DATE COMPLETED:	11/4/94

ELEVATION	DEPTH	SOIL SAMPLES	SAMPLE NO.	SAMPLE METHOD	BLOWS/6"	RECOVERY	PID (PPH)		LITHOLOGY	DESCRIPTION	DEPTH	
							BG	PS				
16.00	0.0		S-1	SS	-	-	-	-	SAND: fine grained, trace silt, gray, damp	0.0		
15.00	1.0		S-2	SS	2	4	15	0.0		06	SILT: some clay, trace fine grained sand, brown, damp	1.8
14.00	2.0		S-3	SS	3	5	9	0.8	00	06	CLAY: little silt, trace roots, gray to brown, stiff	2.0
13.00	3.0		S-4	SS	4	5	5	4	4	7		10
12.00	4.0		S-5	SS	4	6	7	1.1	0.0	1.8	SAND: fine grained, trace to little silt, trace clay, gray, damp to wet, medium dense	7.0
11.00	5.0		S-6	SS	5	7	8	1.3	0.2	0.8		10.0
10.00	6.0		S-7	SS	8	10	11	1.6	0.0	1.2	BOTTOM OF BOREHOLE = 15.0'	11.0
9.00	7.0		S-8	SS	7	7	17	1.5	0.0	4.4		13.0
8.00	8.0										13.0	13.0
7.00	9.0										14.0	14.0
6.00	10.0										15.0	15.0
5.00	11.0										16.0	16.0
4.00	12.0										17.0	17.0
3.00	13.0										18.0	18.0
2.00	14.0										19.0	19.0
1.00	15.0										20.0	20.0
0.00	16.0										21.0	21.0
1.00	17.0										22.0	22.0
2.00	18.0										23.0	23.0
3.00	19.0										24.0	24.0
4.00	20.0										25.0	25.0
5.00	21.0										26.0	26.0
6.00	22.0										27.0	27.0
7.00	23.0										28.0	28.0
8.00	24.0										29.0	29.0
9.00	25.0										30.0	30.0
10.00	26.0										31.0	31.0
11.00	27.0										32.0	32.0
	28.0										33.0	33.0

NOTES:  
1) Groundwater encountered at 14.0' during drilling

BAKER

TEST BORING LOG

BOREHOLE NUMBER:

80-0A-SB06

SHEET: 1 OF 1

PROJECT NUMBER: 62470-274  
 PROJECT NAME: SITE 80 - PARADISE POINT GOLF COURSE MAINTENANCE AREA  
 LOCATION: MCB CAMP LEJEUNE, NC  
 DRILLING COMPANY: HARDIN-HUBER, INC  
 RIG TYPE & NUMBER: ATV  
 DRILLING METHOD: HOLLOW STEM AUGERS  
 WEATHER: SUNNY  
 GEOLOGIST: M. K. DEJOHN  
 ENV. SCIENTIST: M. D. SMITH  
 DATE BEGUN: 11/4/94 DATE COMPLETED: 11/4/94

GROUND SURFACE ELEVATION: 16.47' msl  
 TOTAL DEPTH: 15.0' bgs

ELEVATION	DEPTH	SOIL SAMPLES	SAMPLE NO.	SAMPLE METHOD	BLOWS/6"	RECOVERY	PID (PPH)		LITHOLOGY	DESCRIPTION	DEPTH
							86	PS			
16:00	0.0		S-1	SS	-	-	-	-		SILT: trace clay and roots, dark brown, damp	0.0
15:00	1.0		S-2	SS	4	0.8	0.0	0.3		SILTY CLAY: trace fine grained sand, brown/orange, damp, stiff	1.0
14:00	2.0		S-3	SS	4 8 12	1.3	0.0	86		CLAYEY SILT: trace fine grained sand, trace roots, brown/orange, medium stiff	2.0
13:00	3.0		S-4	SS	5 6 6	1.4	0.0	86		SAND: fine grained, some to trace silt, occasional trace clay, brown/orange/gray/buff, damp to wet, medium dense	3.0
12:00	4.0		S-5	SS	5 10 10 12	1.4	0.0	86			4.0
11:00	5.0		S-6	SS	5 10 12 15	1.3	0.0	86			5.0
10:00	6.0		S-7	SS	3 8 8 10	1.6	0.0	86			6.0
9:00	7.0		S-8	SS	8 12 16 17	1.7	0.0	86			7.0
8:00	8.0				8 9 9 12						8.0
7:00	9.0										9.0
6:00	10.0										10.0
5:00	11.0									11.0	
4:00	12.0									12.0	
3:00	13.0									13.0	
2:00	14.0									14.0	
1:00	15.0									15.0	
0:00	16.0									16.0	
1:00	17.0									17.0	
2:00	18.0									18.0	
3:00	19.0									19.0	
4:00	20.0									20.0	
5:00	21.0									21.0	
6:00	22.0									22.0	
7:00	23.0									23.0	
8:00	24.0									24.0	
9:00	25.0									25.0	
10:00	26.0									26.0	
11:00	27.0									27.0	
12:00	28.0									28.0	

BOTTOM OF BOREHOLE = 15.0'

NOTES:

- 1) Groundwater encountered at 13.0' during drilling.



























BAKER

WELL CONSTRUCTION LOG

BOREHOLE NUMBER:

80-MW031W

SHEET: 3 OF: 3

ELEVATION	DEPTH	SOIL SAMPLES	SAMPLE NO.	SAMPLE METHOD	BLDG/0 5'	RECOVERY (FT)	PID (PPM)		LITHOLOGY	DESCRIPTION	DEPTH	WELL INSTALLATION
							BG	PS				
36:00	50.0									50.0		
37:00	51.0								SAND: Fine grained, little to trace silt, light gray/light brown, damp to wet, medium dense/dense/very dense/loose	51.0		
38:00	52.0									52.0		
39:00	53.0									53.0		
40:00	54.0		S-16	SS	-	-	-	-		SAND: Fine grained, trace silt, trace shell fragments, light grayish green, wet, medium dense/dense/very dense		54.0
41:00	55.0									55.0		
42:00	56.0									56.0		
43:00	57.0									57.0		
44:00	58.0		S-17	SS	8	1.8	0.2	0.2				58.0
45:00	59.0				12							59.0
46:00	60.0				14							60.0
47:00	61.0				23							61.0
48:00	62.0											62.0
49:00	63.0		S-18	SS	22	2.0	0.2	0.2				63.0
50:00	64.0				17							64.0
51:00	65.0				28							65.0
52:00	66.0				38							66.0
53:00	67.0											67.0
54:00	68.0		S-19	SS	22	1.3	0.2	0.2				68.0
55:00	69.0				28							69.0
56:00	70.0				34						70.0	
57:00	71.0				41						71.0	
58:00	72.0										72.0	
59:00	73.0										73.0	
60:00	74.0										74.0	
61:00	75.0										75.0	
62:00	76.0										76.0	
63:00	77.0										77.0	
64:00	78.0										78.0	
65:00	79.0										79.0	
66:00	80.0										80.0	
67:00	81.0										81.0	
68:00	82.0										82.0	
<p>BOTTOM OF BOREHOLE 72.5'</p> <p>NOTES:</p> <p>1) Groundwater encountered @ 19.0' during drilling.</p>												





BAKER

WELL CONSTRUCTION LOG

BOREHOLE NUMBER:

80-MW04

SHEET: 2 OF: 2

ELEVATION	DEPTH	SOIL SAMPLES	SAMPLE NO.	SAMPLE METHOD	BLOGS/O. S'	RECOVERY (FT)	PID (PPM)		LITHOLOGY	DESCRIPTION	DEPTH	WELL INSTALLATION	
							SG	PS					
6-00	20.0		S-12	SS	7	1.0	0.2	0.3		SAND: fine grained, trace silt, light brown, wet, medium dense to loose	20.0		
7-00	21.0				13								21.0
8-00	22.0				19								22.0
9-00	23.0				17								23.0
10-00	24.0		S-13	SS	6	1.4	0.1	0.1					24.0
11-00	25.0				8								25.0
12-00	26.0		S-14	SS	9	1.1	0.1	0.1					26.0
13-00	27.0				6								27.0
14-00	28.0				3								28.0
15-00	29.0				3								29.0
16-00	30.0												30.0
17-00	31.0												31.0
18-00	32.0									32.0			
19-00	33.0									33.0			
20-00	34.0									34.0			
21-00	35.0									35.0			
22-00	36.0									36.0			
23-00	37.0									37.0			
24-00	38.0									38.0			
25-00	39.0									39.0			
26-00	40.0									40.0			
27-00	41.0									41.0			
28-00	42.0									42.0			
29-00	43.0									43.0			
30-00	44.0									44.0			
31-00	45.0									45.0			
32-00	46.0									46.0			
33-00	47.0									47.0			
34-00	48.0									48.0			
35-00	49.0									49.0			
36-00	50.0									50.0			
37-00	51.0									51.0			
38-00	52.0									52.0			

BOTTOM OF BOREHOLE = 27.0'  
 NOTES:  
 1) Groundwater encountered = 13.5' during drilling

BAKER

WELL CONSTRUCTION LOG

BOREHOLE NUMBER:

80-MW05

SHEET: 1 OF 2

PROJECT NUMBER: 62470-274  
 PROJECT NAME: SITE 80 - PARADISE POINT GOLF COURSE MAINTENANCE AREA  
 LOCATION: MCB CAMP LEJEUNE, NC  
 DRILLING COMPANY: HARDIN-HUBER, INC.  
 RIG TYPE & NUMBER: TRUCK RIG  
 DRILLING METHOD: AUGERS  
 WEATHER: SUNNY, HOT, HUMID  
 GEOLOGIST: J.E. ZIMMERMAN  
 ENV. SCIENTIST: L.H. JOHNSON  
 DATE BEGUN: 11/4/94 DATE COMPLETED: 11/4/94

GROUND SURFACE ELEVATION: 16.22' msl  
 TOP OF PVC CASING ELEVATION: 18.54' msl

WELL DETAILS (FT)

STICKUP: 2.5  
 LENGTH OF RISER (2" I.D.): 12.0  
 LENGTH OF SCREEN (2" I.D.): 15.0  
 THICKNESS OF GROUT: 8.0  
 THICKNESS OF SEAL: 2.0  
 THICKNESS OF SAND PACK: 17.0

ELEVATION	DEPTH	SOIL SAMPLES	SAMPLE NO.	SAMPLE METHOD	BLOWS/0.5'	RECOVERY (FT)	PTD (PPH)		LITHOLOGY	DESCRIPTION	DEPTH	WELL INSTALLATION
							BG	PS				
28.00	4.0									4.0		
19.00	3.0									3.0		
18.00	2.0									2.0		
17.00	1.0									1.0		
16.00	0.0		S-1	SS	-	-	0.2	0.2		0.0		
15.00	1.0		S-2	SS	3	5	0.1	0.1		1.0		
14.00	2.0				5	9				2.0		
13.00	3.0		S-3	SS	5	8	0.2	0.2		3.0		
12.00	4.0				14	9				4.0		
11.00	5.0		S-4	SS	13	14	0.2	0.2		5.0		
10.00	6.0				18	15				6.0		
9.00	7.0		S-5	SS	9	10	0.2	0.2		7.0		
8.00	8.0				10	12				8.0		
7.00	9.0		S-6	SS	4	10	0.2	0.2		9.0		
6.00	10.0				10	12				10.0		
5.00	11.0		S-7	SS	3	7	0.2	0.2		11.0		
4.00	12.0				18	21				12.0		
3.00	13.0		S-8	SS	3	5	0.2	0.2		13.0		
2.00	14.0				12	11				14.0		
1.00	15.0		S-9	SS	3	5	0.2	0.2		15.0		
0.00	16.0				10	11				16.0		
1.00	17.0		S-10	SS	6	11	0.2	0.2		17.0		
2.00	18.0				12	17				18.0		
3.00	19.0		S-11	SS	4	5	0.2	0.2		19.0		
4.00	20.0				12	18				20.0		
5.00	21.0		S-12	SS	4	5	0.2	0.2		21.0		
6.00	22.0				8	7				22.0		
7.00	23.0									23.0		
8.00	24.0									24.0		


DESCRIPTION

SILTY SAND: fine grained, trace of root material at surface, trace to little clay, dark brown/brown, damp, very loose to medium dense

SILTY CLAY: trace to little fine grained sand, brown/light gray, damp, stiff/medium dense/very stiff

SAND: fine grained, trace silt, brown/light gray, damp to wet, medium dense

SAND: fine grained, trace to little silt, trace clay, light gray, wet, loose/medium dense



BAKER

WELL CONSTRUCTION LOG

BOREHOLE NUMBER:

BO-MW05

SHEET: 2 OF: 2

ELEVATION	DEPTH	SOIL SAMPLES	SAMPLE NO.	SAMPLE METHOD	BLMS/D 5'	RECOVERY (FT)	PID (PPM)		LITHOLOGY	DESCRIPTION	DEPTH	WELL INSTALLATION							
							BG	PS											
4.00	20.0		S-12	SS	4 5 6 7	1.2	0.2	0.2		SAND: fine grained, trace silt, brown/light gray, damp to wet, medium dense	20.0								
5.00	21.0																		
6.00	22.0																		
7.00	23.0																		
8.00	24.0									S-13	SS		2 4 5 2	1.1	0.2	0.2	SAND: fine grained, trace to little silt, trace clay, light gray, wet, loose/medium dense	23.0	
9.00	25.0									S-14	SS		4 5 8 5	1.3	0.2	0.2			24.0
10.00	26.0																		25.0
11.00	27.0									26.0									
12.00	28.0									27.0									
13.00	29.0									28.0									
14.00	30.0									29.0									
15.00	31.0									30.0									
16.00	32.0									31.0									
17.00	33.0									32.0									
18.00	34.0									33.0									
19.00	35.0									34.0									
20.00	36.0									35.0									
21.00	37.0									36.0									
22.00	38.0									37.0									
23.00	39.0									38.0									
24.00	40.0									39.0									
25.00	41.0									40.0									
26.00	42.0									41.0									
27.00	43.0									42.0									
28.00	44.0									43.0									
29.00	45.0									44.0									
30.00	46.0									45.0									
31.00	47.0									46.0									
32.00	48.0									47.0									
33.00	49.0									48.0									
34.00	50.0									49.0									
35.00	51.0									50.0									
36.00	52.0									51.0									
										52.0									

BOTTOM OF BOREHOLE = 27.5'

NOTES:

- 1) Groundwater encountered @ 14' during drilling

BAKER

WELL CONSTRUCTION LOG

BOREHOLE NUMBER:

80-M406

SHEET: 1 OF 2

PROJECT NUMBER: 62470-274  
 PROJECT NAME: SITE 80 - PARADISE POINT GOLF COURSE MAINTENANCE AREA  
 LOCATION: MCB CAMP LEJEUNE, NC  
 DRILLING COMPANY: HARDIN-HUBER, INC.  
 RIG TYPE & NUMBER: TRUCK RIG  
 DRILLING METHOD: AUGERS  
 WEATHER: SUNNY, HOT, HUMID  
 GEOLOGIST: H. K. DeJOHN  
 ENV. SCIENTIST: H. O. SMITH  
 DATE BEGUN: 11/5/94 DATE COMPLETED: 11/5/94

GROUND SURFACE ELEVATION: 17.06' msl  
 TOP OF PVC CASING ELEVATION: 19.42' msl

WELL DETAILS (FT)

STICKUP: 2.5  
 LENGTH OF RISER (2" I.D.): 11.0  
 LENGTH OF SCREEN (2" I.D.): 15.0  
 THICKNESS OF GROUT: 7.0  
 THICKNESS OF SEAL: 2.0  
 THICKNESS OF SAND PACK: 18.0

ELEVATION	DEPTH	SOIL SAMPLES	SAMPLE NO.	SAMPLE METHOD	BLONS/O'S	RECOVERY (FT)	PTD (PPM)		LITHOLOGY	DESCRIPTION	DEPTH	WELL INSTALLATION
							B6	PS				
21.00	4.0									4.0		
20.00	3.0									3.0		
19.00	2.0									2.0		
18.00	1.0									1.0		
17.00	0.0									0.0		
16.00	1.0		S-1	SS	7	1.2	0.0	0.0	SILT: trace to some clay, dark brown/gray, damp, stiff	1.0		
15.00	2.0		S-2	SS	8	1.2	0.0	0.0		2.0		
14.00	3.0				9					3.0		
13.00	4.0		S-3	SS	6	1.5	0.0	0.0		4.0		
12.00	5.0				5					5.0		
11.00	6.0		S-4	SS	3	1.4	0.0	0.0	SILTY CLAY: brown/gray/orange, damp, stiff	6.0		
10.00	7.0				6					7.0		
9.00	8.0		S-5	SS	7	1.9	0.0	0.0		8.0		
8.00	9.0				9					9.0		
7.00	10.0		S-6	SS	10	1.4	0.0	0.0	SAND: fine to medium grained, little to some silt, tan/orange/gray, damp to wet, medium dense	10.0		
6.00	11.0				11					11.0		
5.00	12.0		S-7	SS	6	1.1	0.0	0.0		12.0		
4.00	13.0				8					13.0		
3.00	14.0		S-8	SS	7	1.8	0.0	0.0		14.0		
2.00	15.0				8					15.0		
1.00	16.0		S-9	SS	4	1.1	0.0	0.0	CLAY: trace silt, trace fine grained sand @ 18.0", wet, medium dense	16.0		
0.00	17.0				2					17.0		
1.00	18.0		S-10	SS	1	2.0	0.0	0.0		18.0		
2.00	19.0				2					19.0		
3.00	20.0		S-11	SS	4	1.1	0.0	0.0	SAND: fine to medium grained, some to little silt, orange/brown/gray, wet, medium dense to dense	20.0		
4.00	21.0				4					21.0		
5.00	22.0		S-12	SS	7	1.1	0.0	0.0		22.0		
6.00	23.0				10					23.0		
7.00	24.0				6					24.0		

BAKER

WELL CONSTRUCTION LOG

BOREHOLE NUMBER:

80-MW06

SHEET: 2 OF 2

ELEVATION	DEPTH	SOIL SAMPLES	SAMPLE NO	SAMPLE METHOD	BLOBS/0.5'	RECOVERY (FT)	PID (PPM)		LITHOLOGY	DESCRIPTION	DEPTH	WELL INSTALLATION
							BS	PS				
1-00	20.0		S-12	SS	9 17 28 33	1.1	0.0	0.0		SAND: Fine to medium grained, some to little silt, orange/brown/gray, wet, medium dense to dense	20.0	
5-00	21.0		S-13	SS	12 19 22 24	1.0	0.0	0.0			21.0	
6-00	22.0		S-14	SS	16 18 23 26	1.0	0.0	0.0			22.0	
7-00	23.0									23.0		
8-00	24.0									24.0		
9-00	25.0									25.0		
10-00	26.0									26.0		
11-00	27.0									27.0		
12-00	28.0									28.0		
13-00	29.0									29.0		
14-00	30.0									30.0		
15-00	31.0									31.0		
16-00	32.0									32.0		
17-00	33.0									33.0		
18-00	34.0									34.0		
19-00	35.0									35.0		
20-00	36.0									36.0		
21-00	37.0									37.0		
22-00	38.0									38.0		
23-00	39.0									39.0		
24-00	40.0									40.0		
25-00	41.0									41.0		
26-00	42.0									42.0		
27-00	43.0									43.0		
28-00	44.0									44.0		
29-00	45.0									45.0		
30-00	46.0									46.0		
31-00	47.0									47.0		
32-00	48.0									48.0		
33-00	49.0									49.0		
34-00	50.0									50.0		
35-00	51.0									51.0		
36-00	52.0									52.0		

BOTTOM OF BOREHOLE = 27.5'  
 NOTES:  
 1) Groundwater encountered @ 14.5' during drilling







# BAKER

## WELL CONSTRUCTION LOG

BOREHOLE NUMBER:

80-MW08

SHEET: 1 OF 2

PROJECT NUMBER: 62470-274  
 PROJECT NAME: SITE 80 - PARADISE POINT GOLF COURSE MAINTENANCE AREA  
 LOCATION: MCB CAMP LEJEUNE, NC  
 DRILLING COMPANY: PARRATT-WOLFF, INC  
 RIG TYPE & NUMBER: TRUCK RIG - CHE 55  
 DRILLING METHOD: AUGERS  
 WEATHER: OVERCAST, COOL, DRIZZLE, BREEZY  
 GEOLOGIST: M. K. DEJOHN  
 ENV. SCIENTIST: -  
 DATE BEGUN: 6/13/95 DATE COMPLETED: 6/13/95

GROUND SURFACE ELEVATION: 15.00' *msl*  
 TOP OF PVC CASING ELEVATION: 17.33' *msl*

WELL DETAILS (FT)

STICKUP: 2.33  
 LENGTH OF RISER (2" I.D.): 10.0  
 LENGTH OF SCREEN (2" I.D.): 15.0  
 THICKNESS OF GROUT: 6.0  
 THICKNESS OF SEAL: 2.0  
 THICKNESS OF SAND PACK: 17.0

ELEVATION	DEPTH	SOIL SAMPLES	SAMPLE NO.	SAMPLE METHOD	BLDG./O.S.	RECOVERY (FT)	PID (PPM)		LITHOLOGY	DESCRIPTION	DEPTH	WELL INSTALLATION
							86	35				
19:00	4.0									4.0		
18:00	3.0									3.0		
17:00	2.0									2.0		
16:00	1.0									1.0		
15:00	0.0		S-1	HA	-	-	1.1	1.1		0.0		
14:00	1.0		S-2	SS	1	1.0	0.5	0.5		1.0		
13:00	2.0				2					2.0		
12:00	3.0		S-3	SS	2	1.6	0.5	0.5		3.0		
11:00	4.0				3					4.0		
10:00	5.0		S-4	SS	5	1.8	0.6	0.6		5.0		
9:00	6.0				4					6.0		
8:00	7.0		S-5	SS	5	1.6	0.5	0.5		7.0		
7:00	8.0				4					8.0		
6:00	9.0		S-6	SS	3	1.7	0.5	0.5		9.0		
5:00	10.0				2					10.0		
4:00	11.0		S-7	SS	3	1.3	0.5	0.5		11.0		
3:00	12.0				2					12.0		
2:00	13.0		S-8	SS	2	1.8	0.4	0.4		13.0		
1:00	14.0				3					14.0		
0:00	15.0		S-9	SS	5	2.0	-	-		15.0		
1:00	16.0				6					16.0		
2:00	17.0		S-10	SS	6	1.0	-	-		17.0		
3:00	18.0				8					18.0		
4:00	19.0		S-11	SS	9	2.0	-	-		19.0		
5:00	20.0				11					20.0		
6:00	21.0				16					21.0		
7:00	22.0		S-12	SS	2	1.0	-	-		22.0		
8:00	23.0				3					23.0		
9:00	24.0									24.0		

# DESCRIPTION

SILTY SAND: fine grained, trace gravel, trace coarse sand, trace clay, brownish gray, damp

SANDY SILT: fine grained sand, trace to little clay, brown to orangish brown, damp, loose

CLAY: some to trace silt, little fine to medium grained sand @ 8.2-9', gray layers of rock fragments @ 9-13.8', reddish gray to orangish brown, damp to wet, medium stiff

SILT: little clay and fine sand, gray, wet, medium stiff

SAND: fine grained, trace to some silt, trace to little clay, gray w/iron staining/black and orangish brown, wet, medium dense/loose @ 21-23'

